















Sling eye adjuste

FPM 50 - Multi-tasking machine TALURIT™

This all-round machine can be a pre-pressing machine, marking machine, cutting machine or a swager or all depending on the requirements of the customer. It is perfect for small and medium sized rigging shop.

All performing units are optional extras:

Pre-pressing Pre-pressing and fixing of the wire rope in aluminium ferrules up to size 50. Pre-pressing can

take place horizontally or vertically to meet own requirements and wishes.

Marking Marking of pressed ferrules as per EN standard. Dies for marking is ordered separately. The time

consuming and expensive marking procedure is carried out rapidly and with ease. The marking of pre-pressed ferrules can be executed on one or both sides of the press ferrule simultaneously

in specific marking dies with changeable steel types (letters/figures).

Cutting Cuts wire rope Ø1-20 mm.

Swaging The use of FPM 50 as a hydraulic open swager for ferrules size 1-6 with dies block size A.

Dies are ordered separately.

Sling eye adjuster Tool to adjust the sling eye.

Sling eye table Table with ruler and rod to adjust the sling eye.

The machine can thus be utilized economically by mounting the optional units.

PRE-PRESSING MACHINE			
Art No:	FPM 50	Options:	Art No:
Rated current at 230/400V (A)	11,2/6,4	Pre-pressing	2879
Max oil pressure (bar)	380	Marking	
Piston velocity (mm/s)	17	marking die 8-16	1784
Max. pressure power (kN)	220	marking die 18-24	1812
Power (kW)	3	marking die 26-50	1815
Max. length of stroke (mm)	112	Cutting	4417
Oil volume (I)	23 (oil is not delivered with the machine)	Swaging - die Holders	2895
Dimensions L*W*H (mm	1 030 x 820 x 1 140	dies	block size A
Weight (kg)	370	Sling eye adjuster	2891
		Sling eye table	2883